Technische Universität München
Fakultät für Informatik

Dr. K. N. Verma
verma@in.tum.de
Room: MI 02.07.041

Language Based Security

Summer Semester 2006

1. Homework *03 May 2006*

Exercise 1:

Consider the following C program. `strtol (s, NULL, 10)` returns the integer written as string `s` in decimal notation. Call the program with appropriate inputs to print `x=10`.

```
#include <stdio.h>
void f (int i, int j) {
  int a[50];
  a[i] +=  j;
}
int main (int argc, char *argv[]) {
  int x = 10, y, z;
  if (argc > 1) {
    y = strtol (argv[1], NULL, 10);
    z = strtol (argv[2], NULL, 10);
    f(y, z);
    x = 20;
    printf ("x=%d\n", x);
  }
  return 0;
}
```

Here is the output of gdb on the executable produced after compilation. (Or work with your own compiled version of the program.)

```
Dump of assembler code for function main:
0x8048396 <main>:       push   %ebp
0x8048397 <main+1>:     mov    %esp,%ebp
0x8048399 <main+3>:     sub    $0x18,%esp
0x804839c <main+6>:     and    $0xfffffff0,%esp
0x804839f <main+9>:     mov    $0x0,%eax
0x80483a4 <main+14>:    sub    %eax,%esp
0x80483a6 <main+16>:    movl   $0xa,0xfffffffc(%ebp)
0x80483ad <main+23>:    cmpl   $0x1,0x8(%ebp)
0x80483b1 <main+27>:    jle    0x8048412 <main+124>
```

```
0x80483b3 <main+29>:    sub    $0x4,%esp
0x80483b6 <main+32>:    push   $0xa
0x80483b8 <main+34>:    push   $0x0
0x80483ba <main+36>:    mov    0xc(%ebp),%eax
0x80483bd <main+39>:    add    $0x4,%eax
0x80483c0 <main+42>:    pushl  (%eax)
0x80483c2 <main+44>:    call   0x804827c <strtol>
0x80483c7 <main+49>:    add    $0x10,%esp
0x80483ca <main+52>:    mov    %eax,0xfffffff8(%ebp)
0x80483cd <main+55>:    sub    $0x4,%esp
0x80483d0 <main+58>:    push   $0xa
0x80483d2 <main+60>:    push   $0x0
0x80483d4 <main+62>:    mov    0xc(%ebp),%eax
0x80483d7 <main+65>:    add    $0x8,%eax
0x80483da <main+68>:    pushl  (%eax)
0x80483dc <main+70>:    call   0x804827c <strtol>
0x80483e1 <main+75>:    add    $0x10,%esp
0x80483e4 <main+78>:    mov    %eax,0xfffffff4(%ebp)
0x80483e7 <main+81>:    sub    $0x8,%esp
0x80483ea <main+84>:    pushl  0xfffffff4(%ebp)
0x80483ed <main+87>:    pushl  0xfffffff8(%ebp)
0x80483f0 <main+90>:    call   0x8048374 <f>
0x80483f5 <main+95>:    add    $0x10,%esp
0x80483f8 <main+98>:    movl   $0x14,0xfffffffc(%ebp)
0x80483ff <main+105>:   sub    $0x8,%esp
0x8048402 <main+108>:   pushl  0xfffffffc(%ebp)
0x8048405 <main+111>:   push   $0x80484e4
0x804840a <main+116>:   call   0x804829c <printf>
0x804840f <main+121>:   add    $0x10,%esp
0x8048412 <main+124>:   mov    $0x0,%eax
0x8048417 <main+129>:   leave
0x8048418 <main+130>:   ret
End of assembler dump.
Dump of assembler code for function f:
0x8048374 <f>:          push   %ebp
0x8048375 <f+1>:        mov    %esp,%ebp
0x8048377 <f+3>:        sub    $0xd8,%esp
0x804837d <f+9>:        mov    0x8(%ebp),%ecx
0x8048380 <f+12>:       mov    0x8(%ebp),%edx
0x8048383 <f+15>:       mov    0xc(%ebp),%eax
0x8048386 <f+18>:       add    0xffffff28(%ebp,%edx,4),%eax
0x804838d <f+25>:       mov    %eax,0xffffff28(%ebp,%ecx,4)
0x8048394 <f+32>:       leave
0x8048395 <f+33>:       ret
End of assembler dump.
```